

Technical Data

Model			
	PV0191-1P-A	PV0191-1P	HDKDC1P32AL
Rated Voltage	1000VDC	1000VDC	1500VDC
Rated Current	32A	32A	50A
Size of Fuse Link	10x38mm	10x38mm	10/14x85mm
Class of Operation	gPV	gPV	gPV
Mechanical Life	500	500	500
Product Width	18mm	18mm	22mm
Tightening Torque	2.5Nm 14In-lbs	2.5Nm 14In-lbs	2.5Nm 14In-lbs
Terminal size for Cable	6mm ² 8-18AWG	6mm ² 8-18AWG	10mm ² 6-18AWG
Ambient temperature (with daily average ≤35°C)	-5°C~+40°C		
Storage Temperature	-25°C~+70°C		
Standard:	IEC60269-6		
Mounting	On DIN rail EN60715(35mm) by means of fast clip device		

Reference No.	DC Voltage Grade	Size of Fuse Link	Current Rating for Fuse Link
PV0191-1P-A	1000VDC	10x38mm	1,2,3,4,5,6,8,10,12,15,16,20,25,30,32A
PV0191-1P	1000VDC	10x38mm	1,2,3,4,5,6,8,10,12,15,16,20,25,30,32A
HDKDC1P32AL	1500VDC	14x85mm	8,10,12,15,16,20,25,30,32,35,40,45,50A

Technical Data

Model			
	BX0234-25A	FSKDC25AL	FSKDC25AL-14
Size	10x38mm	10x85mm	14x85mm
Rated Voltage	1000VDC	1500VDC	1500VDC
Rated Current	1-32A	2-32A	8-50A
Class of Operation	gPV	gPV	gPV
Breaking capacity	20KA	20KA	20KA
Standard:	IEC60269		

Current Rating	Reference No. for Fuse Link		
	Voltage Grade and Size of Fuse Link		
	BX0234-25A 1000VDC 10x38mm	FSKDC25AL 1500VDC 10x85mm	FSKDC25AL-14 1500VDC 14x85mm
1A	BX0234-1A		
2A	BX0234-2A	FSKDC2AL	
3A	BX0234-3A	FSKDC3AL	
4A	BX0234-4A	FSKDC4AL	
5A	BX0234-5A	FSKDC5AL	
6A	BX0234-6A	FSKDC6AL	
8A	BX0234-8A	FSKDC8AL	FSKDC8AL-14
10A	BX0234-10A	FSKDC10AL	FSKDC10AL-14
12A	BX0234-12A	FSKDC12AL	FSKDC12AL-14
15A	BX0234-15A	FSKDC15AL	FSKDC15AL-14
16A	BX0234-16A	FSKDC16AL	FSKDC16AL-14
20A	BX0234-20A	FSKDC20AL	FSKDC20AL-14
25A	BX0234-25A	FSKDC25AL	FSKDC25AL-14
30A	BX0234-30A	FSKDC25AL	FSKDC30AL-14
32A	BX0234-32A	FSKDC32AL	FSKDC32AL-14
35A			FSKDC35AL-14
40A			FSKDC40AL-14
45A			FSKDC45AL-14
50A			FSKDC50AL-14